

RieFa[®] - Green roof
Processing instructions!



You need:

- 2 – 3 people to produce approx. 25 m² / hour of finished green space.
- Root and waterproof film
- A knife or scissors for cutting textile fleece
- A mobile cut-off machine with a smooth cutting disc
(for cutting the RieFa[®] panels and the sedum vegetation mats)
- A rake to distribute the potting soil or compost
- Slow release fertilizer twice a year, in spring RieFa[®] Sedum Conditioner, in autumn RieFa[®] Sedum Stronger
(Product data sheet of our fertilizer can be found at www.fornatec.de/dachbegruenung/)

Tips:

- Prepare and plan your work processes so that the delivered Sedum mats can be rolled out and laid within 24 hours of delivery.
- Always lay the individual layers in sections, ready to go:
(fleece, RieFa[®] plate, soil, sedum).
- The finished surfaces can be walked on without any problem, but you do not always have to enter the newly laid individual layers.
- A 10 cm strip between the gutter, gravel stop, etc. for the green roofs with coarse pebbles 25 – 40 mm as edge strips looks good and is another filter option. Before rainwater is drained into the gutter or into the gutter inlet.

Alternatively:

Can you use a seed mix (but this is not recommended). Spread at least 4 cm of flower or compost soil on the coconut fiber side and distribute and incorporate your desired seed mixture on the surface.